

## EisBaer EisTouch HI 6G – 15" Touchpanel with PoE



### Specification:

- Fanless Design, compact and maintenance free
- Intel® Celeron N6211 (up to 3.0GHz)
- Intel® HD Graphics
- 4GB RAM
- 128 GB (M.2 SSD)
- OS: Windows 11 IoT Enterprise
- 15" Display 1024 \* 768 Pixel
- Power supply: **PoE IEEE 802.3at** from 25Watt  
PoE support condition: Use without other power consuming devices
- 2x USB 3.2
- 2x 2.5GigaLAN (1x Ethernet, 1x PoE-Ethernet)
- 1x RS 232/422/485 (Default: RS485)
- 2x Internal speaker 1W
- 1x Power supply via 12 VDC external
- Operational temperature: 0°C ~ 50°C
- Humidity: 0 ~ 90%, not condensing
- Front: IP65
- Size-Display (W x H x D): 364.4 x 277.86 x 44.5\*mm - includes display frame: 13mm
- Optional: EisTouch 6G – FM-wallbox (348 x 263 x 65 mm)
- Optional: EisTouch 6G – KNX-Interface
- Optional: EisTouch 6G – Cavity wall mounting kit
- Optional: EisTouch 6G - NT (power supply)



*Flush-mounted housing*

**Please note: The touch panel 6G does not have a microphone and therefore it can not be used as a door intercom indoor station.**

### Cut-out dimensions (flush-mounted housing - 15" EisTouch 6G):

**Width:** 348mm (B) **Height:** 263 mm (A) **Depth:** 65 mm (C)  
Surrounding support edge: 5mm per side



### Optional accessories for flush-mounted housing - 15 "EisTouch 6G:

- Cavity wall mounting kit

