

**EisBaer HI-SERVER 3.9 – for distribution board installation. Optimised continuous operation as an industrial built-in device, suitable for licence sizes EisBaer Pro Domo, Starter and Professional**



- Industry suitable and dust-protected
- Fanless design
- Intel® Celeron® processor J6412
- Fanless, passive cooling
- 8 GB DDR3 RAM
- 256 GB SSD
- Operating system: Windows 11 Professional
- Power supply: 12 V DC SELV
- Energy efficient (max. consumption: TDP 10 Watt)
- Compact, robust and low-maintenance
- 2x USB 3.0 und 2x USB 2.0
- 2x RS232 COM
- 2x Ethernet (10/100/1000MBit)
- 2 x HDMI 1.4 + DP 1.2 synchron



- |                       |                     |
|-----------------------|---------------------|
| 1 Power On/Off Switch | 2 2 x USB3.0        |
| 3 2 x USB2.0          | 4 2 x DB9 RS232 COM |



- |                      |              |
|----------------------|--------------|
| 5 SPK                | 6 MIC        |
| 7 2 x RJ45 Giga LANs | 8 DP 1.2     |
| 9 2 x HD 1.4         | 10 12V DC In |

- Operating temperature: -20°C - 60°C
- Humidity: 15 - 85% @30°C, non-condensing
- Unit dimensions: 144 mm / 8 TE
- FCC Class B, UL, CE and RoHS compliant Visualization: EisBär SCADA V3-Suite pre-installed (without project license and dongle)

- Optional: WLAN 802.11ac + BT
- Optional: EisBär HI-Server 3.3 - mounting kit (VESA mount)
- Optional: EisBär HI-Server 3.9 - 19" mounting rack